Printing date 02.04.2024 Version number 180 Revision: 02.04.2024

Hazardous according to criteria of Australian Safety and Compensation Council.

### 1 Identification

- · Product identifier
- · Trade name: Nexus Sure Lift With Dye J6D
- · Article number: 309030
- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: Nexus Construction Systems Unit 4, 25-27 Olive Grove Keysborough VIC 3173

Melbourne: (03) 9988 7701 Brisbane: (07) 3910 2442 Perth: (08) 6144 3690 Sydney: (02) 4647 0395

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.

· Emergency telephone number:

Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.

Australia in-country +(61)-290372994

#### 2 Hazard(s) Identification

- · Classification of the substance or mixture
- Flam. Liq. 3 H226 Flammable liquid and vapour.
- Skin Irrit. 2 H315 Causes skin irritation.
- Eye Dam. 1 H318 Causes serious eye damage.
- Muta. 1A H340 May cause genetic defects.
- Carc. 1A H350 May cause cancer.
- STOT RE 1 H372 Causes damage to the central nervous system through prolonged or repeated exposure.
- Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.
- · Label elements
- · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms







GHS02

GHS05

...

- · Signal word Danger
- · Hazard-determining components of labelling: Stoddard solvent

(Contd. on page 2)

 Printing date 02.04.2024
 Version number 180
 Revision: 02.04.2024

#### Trade name: Nexus Sure Lift With Dye J6D

(Contd. of page 1)

butanol

Naphtha (petroleum), hydrodesulfurized heavy

Solvent naphtha (petroleum), light arom.

#### · Hazard statements

Flammable liquid and vapour.

Causes skin irritation.

Causes serious eye damage.

May cause genetic defects.

May cause cancer.

Causes damage to the central nervous system through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

#### · Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

#### 3 Composition and Information on Ingredients

- · Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

8032-41-3	Stoddard solvent	≥20-<35%
	Flam. Liq. 3, H226; Muta. 1B, H340; Carc. 1B, H350; STOT RE 1, H372; Asp. Tox. 1, H304	
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	≥20-<35%
	♦ Muta. 1B, H340; Carc. 1B, H350; STOT RE 1, H372; Asp. Tox. 1, H304	
64742-95-6	Solvent naphtha (petroleum), light arom.	>8-≤14%
	♦ Flam. Liq. 3, H226; ♦ Muta. 1B, H340; Carc. 1B, H350; Asp. Tox. 1, H304; ♦ Acute Tox. 4, H332	
95-63-6	1,2,4-trimethylbenzene	>5.5- <b>≤</b> 9.5%
	Flam. Liq. 3, H226; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	
78-83-1	butanol	≥3-≤5%
	♠ Flam. Liq. 3, H226; ♠ Eye Dam. 1, H318; ♠ Skin Irrit. 2, H315; STOT SE 3, H335-H336	
64742-47-8	Distillates (petroleum), hydrotreated light	≥0.4-≤2%
	♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304	
98-82-8	cumene	≥1-<1.7%
	Flam. Liq. 3, H226; & Carc. 2, H351; Asp. Tox. 1, H304; Acute Tox. 4, H302; STOT SE 3, H335	

(Contd. on page 3)

Printing date 02.04.2024 Version number 180 Revision: 02.04.2024

Trade name: Nexus Sure Lift With Dye J6D

	(Contd. of page 2)
64742-48-9 Naphtha (petroleum), hydrotreated heavy	≥0.1-<1%
🕸 Muta. 1A, H340; Carc. 1A, H350; Asp. Tox. 1, H304; Flam. Liq. 4, H227	
91-20-3 naphthalene	≥0.1-<0.2%
♦ Carc. 2, H351; ♦ Acute Tox. 4, H302; Flam. Liq. 4, H227	

• Additional information: For the wording of the listed hazard phrases refer to section 16.

#### 4 First Aid Measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

*Immediately rinse with water.* 

If skin irritation continues, consult a doctor.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Seek medical treatment.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

### 5 Fire Fighting Measures

- · Extinguishing media
- · Suitable extinguishing agents: Foam
- · For safety reasons unsuitable extinguishing agents: Water
- Special hazards arising from the substance or mixture Formation of toxic gases is possible during heating or in case of fire.
- · Advice for firefighters
- · Protective equipment: No special measures required.

#### 6 Accidental Release Measures

- · Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

\_\_\_^

 Printing date 02.04.2024
 Version number 180
 Revision: 02.04.2024

Trade name: Nexus Sure Lift With Dye J6D

(Contd. of page 3)

### 7 Handling and Storage

- · Handling:
- · Precautions for safe handling

Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage: cool and dry
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

#### 8 Exposure controls and personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters

· Ingredients with	limit values that req	quire monitoring a	it the workplace:
--------------------	-----------------------	--------------------	-------------------

#### 8052-41-3 Stoddard solvent

NES Long-term value: 790 mg/m³

WES Long-term value: 790 mg/m<sup>3</sup>

#### 78-83-1 butanol

NES | Long-term value: 152 mg/m³, 50 ppm

WES Long-term value: 152 mg/m<sup>3</sup>, 50 ppm

#### 98-82-8 cumene

NES | Short-term value: 375 mg/m³, 75 ppm

Long-term value: 125 mg/m³, 25 ppm

Sk

WES Short-term value: 375 mg/m³, 75 ppm

Long-term value: 125 mg/m³, 25 ppm

Sk

#### 91-20-3 naphthalene

NES | Short-term value: 79 mg/m³, 15 ppm

Long-term value: 52 mg/m³, 10 ppm

WES Short-term value: 79 mg/m³, 15 ppm

Long-term value: 52 mg/m³, 10 ppm

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

(Contd. on page 5)

Printing date 02.04.2024 Version number 180 Revision: 02.04.2024

Trade name: Nexus Sure Lift With Dye J6D

(Contd. of page 4)

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

#### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Eye protection: Wear appropriate eye protection to prevent eye contact.

#### 9 Physical and Chemical Properties

· Information on basic physical and chemical propertie	· Information	on basic	physical and	l chemical	properties
--	---------------	----------	--------------	------------	------------

· General Information

· Appearance:

Form: Liquid

Colour: According to product specification

Odour: CharacteristicOdour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined. Initial boiling point and boiling range: 162 °C

· Flash point: 40 °C

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 230 °C

• **Decomposition temperature:** Not determined.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are

possible.

· Explosion limits:

 Lower:
 1.1 Vol %

 Upper:
 6 Vol %

· Vapour pressure at 20 °C: 1 hPa

• Density at 20 °C: 0.81122 g/cm³
• Relative density Not determined.

Vapour density Not determined.
 Evaporation rate Not determined.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

(Contd. on page 6)

Printing date 02.04.2024 Version number 180 Revision: 02.04.2024

Trade name: Nexus Sure Lift With Dye J6D

	(Contd. of page 5)
Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
· Solvent content: Organic solvents: · Other information	17.9-32.9 % No further relevant information available.

### 10 Stability and Reactivity

- · Reactivity No decomposition if stored and applied as directed.
- · Chemical stability No decomposition if stored and applied as directed
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological Information

- · Information on toxicological effects
- · Acute toxicity

· LD/LC50 1	· LD/LC50 values relevant for classification:			
64742-95-0	64742-95-6 Solvent naphtha (petroleum), light arom.			
Oral	LD50	>6,800 mg/kg (rat)		
Dermal	LD50	>3,400 mg/kg (rab)		
Inhalative	LC50/4 h	>10.2 mg/l (rat)		
95-63-6 1,2	95-63-6 1,2,4-trimethylbenzene			
Oral	LD50	5,000 mg/kg (rat)		
98-82-8 cu	mene			
Oral	LD50	1,400 mg/kg (rat)		
Dermal	LD50	12,300 mg/kg (rabbit)		
	LC50/4 h	24.7 mg/l (mouse)		

- · Primary irritant effect:
- · Skin corrosion/irritation May cause skin irritation.
- · Serious eye damage/irritation Irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

Carcinogenic.

The product can cause inheritable damage.

- AU

Trade name: Nexus Sure Lift With Dye J6D

(Contd. of page 6)

### 12 Ecological Information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Harmful to aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

#### 14 Transport information

- · UN-Number
- · ADG, IMDG, IATA

UN1268

3

- · UN proper shipping name
- $\cdot$  ADG

1268 PETROLEUM DISTILLATES, N.O.S.,

ENVIRONMENTALLY HAZARDOUS

· IMDG, IATA PETROLEUM DISTILLATES, N.O.S.

- · Transport hazard class(es)
- · ADG, IMDG, IATA



· Class 3 Flammable liquids.

· Label

(Contd. on page 8)

Printing date 02.04.2024 Version number 180 Revision: 02.04.2024

Trade name: Nexus Sure Lift With Dye J6D

	(Contd. of page
Packing group	
ADG, IMDG, IATA	III
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	30
EMS Number:	F- $E$ , $S$ - $E$
Stowage Category	A
Transport in bulk according to Annex II of	Marpol and the
IBC Code	Not applicable.
Transport/Additional information:	
ADG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1268 PETROLEUM DISTILLATES, N.O.S., 3, II
	ENVIRONMENTALLY HAZARDOUS

4 # 10			C	. •
15 Ke	gulai	ory in	ormai	1011

· Safety, health and	l environmental	regulations/	legislation	specific for t	he substance or miv	ture
Sureiv, neuiin unu	i environmeniai	162mmmmm	iezisiuii011	SDECHIC IOI L	ne subsulice of mix	uure

Australian I	Inventory of Chemical Substances
8052-41-3	Stoddard solvent
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy
64742-95-6	Solvent naphtha (petroleum), light arom.
95-63-6	1,2,4-trimethylbenzene
9003-29-6	Butene, homopolymer
112-62-9	Methyl 9-octadecenoate
78-83-1	butanol
112-80-1	oleic acid, pure
25551-13-7	Trimethylbenzene
64742-47-8	Distillates (petroleum), hydrotreated light
98-82-8	cumene
64742-48-9	Naphtha (petroleum), hydrotreated heavy
1330-20-7	xylene
103-65-1	propylbenzene

(Contd. on page 9)

 Printing date 02.04.2024
 Version number 180
 Revision: 02.04.2024

Trade name: Nexus Sure Lift With Dye J6D

	108-67-8 91-20-3	1,2,3-trimethylbenzene mesitylene naphthalene 2-naphthalenol	(Contd. of pag	e 8)
	100-41-4	ethylbenzene		
Ī	· Standard fo	or the Uniform Scheduling of Medicines and Poisons		
	1330-20-7	·	2	56
	91-20-3	naphthalene	2	56

- GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms







GHS02 GHS05

- · **Signal word** Danger
- · Hazard-determining components of labelling:

Stoddard solvent

butanol

Naphtha (petroleum), hydrodesulfurized heavy

Solvent naphtha (petroleum), light arom.

· Hazard statements

Flammable liquid and vapour.

Causes skin irritation.

Causes serious eye damage.

May cause genetic defects.

May cause cancer.

Causes damage to the central nervous system through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

#### · Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

IF SWALLOWED: Immediately call a POISON CENTER/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

*Take off contaminated clothing and wash it before reuse.* 

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

(Contd. on page 10)

Printing date 02.04.2024 Version number 180 Revision: 02.04.2024

Trade name: Nexus Sure Lift With Dye J6D

(Contd. of page 9)

- · National regulations:
- · Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Technical instructions (air):

Class	Share in %
NK	32.9

- · Waterhazard class: Water hazard class 3 (Self-assessment): extremely hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

The provided information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environmental, Health & Safety Department
- · Contact: Environmental, Health & Safety Manager
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Flam. Liq. 4: Flammable liquids - Category 4

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Muta. 1A: Germ cell mutagenicity - Category 1A

Muta. 1B: Germ cell mutagenicity - Category 1B

Carc. 1A: Carcinogenicity - Category 1A

Carc. 1B: Carcinogenicity - Category 1B

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Asp. Tox. 1: Aspiration hazard - Category 1

ΑU